

Dikey Tip Mekanik Tork Artırıcılar

Vertical Type Mechanical Torque Multipliers



- » Tork uygulama hassasiyeti $\pm\%5$ standart.
- » 800 - 16.000 N.m arası sekiz farklı model.
- » Sıkma ve sökmeye uygun planet dişli sistemi.
- » Standart olarak çelik destek ayağı ile sevk edilir.
- » 75 kata kadar aktarım oranlarıyla torklama işlemini kolaylaştırır.
- » Geri dönüş kilit mekanizması güvenli çalışma ortamı sunar.
- » Dayanıklı, sağlam ve uzun ömürlü yapı.

- » Accuracy guaranteed better than $\pm\%5$.
- » Eight different model up to 16.000 N.m.
- » High ratios allow the use of a small torque wrench.
- » Supplied as standard with an steel reaction arm.
- » Anti Backlash system allowing safer and more practical operation.
- » Compact dimensions allow excellent access to applications.
- » Robust construction means minimal maintenance and long life.

RS kodlu ürünlerde geri dönüş kilit sistemi vardır.

RS: Anti Backlash Device (Return Lock System).

Parça Part	Kapasite Capacity		Aktarım Ratio	Kilit Sistemi Lock System	Torkmetre Torque Square	Lokma Socket	D	H1	H2	B	Ağırlık Weight
	Min - N.m	Max - N.m									
MX8	80	800	3.5:1	-	1/2"	3/4"	65	105	132	130	1.3
MX18	180	1.800	3.5:1	-	3/4"	1"	90	150	188	132	3
MX28	280	2.800	13:1	RS	1/2"	1"	95	200	240	132	5.2
MX38	380	3.800	13:1	RS	3/4"	1"	95	200	240	132	5.2
MX50	500	5.000	17:1	RS	3/4"	1.1/2"	120	215	272	150	7
MX80	800	8.000	49:1	RS	3/4"	1.1/2"	132	268	344	200	11.5
MX120	1.200	12.000	58:1	RS	3/4"	1.1/2"	156	272	348	200	14
MX160	1.600	16.000	75:1	RS	3/4"	2.1/2"	215	292	370	225	26

